

LINKVIL 4K Wireless Screen-sharing Pod CP20

Linkvil CP20 is a 4K wireless screen-sharing pod that supports ultra-HD wireless casting with plug-and-play functionality — no drivers or software required. It seamlessly integrates with the CA200 and CA400 wireless conferencing sets to enable multi-transmitter screen sharing. CP20 can also work with UAC and UVC devices from the transmitting end, offering an all-in-one, multi-end screen-sharing solution for conference scenarios. It simplifies the meeting experience, eliminates cable clutter, and delivers a secure and efficient collaboration environment.



4K Wireless
Screen-sharing



Plug & Play



One-click
Screen Freeze



Wireless Access

HIGHLIGHTS

- One-press to start 4K/30fps wireless screen-share
- One-click switch between screen share and freeze mode
- Perfect with CA400/CA200 suite, supports up to 4 devices for seamless expansion
- Plug-n-play without software installation
- Synchronize system volume control for screen sharing devices
- Wireless access to UVC camera/microphone/speaker

SPECIFICATIONS

4K UHD Screen Sharing

- Resolution: Up to 4K/30fps with low latency
- Security: WPA3 data encryption
- Desktop sharing: Mirror and extended mode

Connectivity

- Wi-Fi: Wi-Fi 5/Wi-Fi 6
- Frequency band: 5GHz
- Encryption protocol: WPA3-PSK
- Transmission Distance: up to 10 meters
- Frequency bands & max. transmitted power (EU):
 - Wi-Fi 5GHz, Max 20dBm (Support for selecting corresponding 5G channels based on the country.)

Physical Specifications

- I/O Interface: Type C PD + DP ALT
- Operating Voltage: 5V
- Power consumption: 2.5W
- Buttons: Screen-Sharing/Volume up/Volume down/Freeze Screen
- LED indicator: 1 Red, 1 Green ↑
- Freeze Screen Button
 - Green light: Resume casting
 - Red light: Pause casting

• Dimensions

- CP20 Screen-Sharing Pod: 189*40*18mm
- CP20 Screen-Sharing Pod USB cable length: 85mm
- Gift-box: 231*74.5*25.5mm
- Carton package: 602*432*260mm (112 PCS)

• Weight

- CP20 Screen-Sharing Pod: 62g
- Carton net weight: 14.79kg
- Carton gross weight: 16kg

• Temperature and humidity

- Working temperature: -10°C ~ +40°C
- Working humidity: 0% ~ 90%RH

Package Contents

- Screen-sharing Pod: CP20
- Quick Start Guide










Compatibility

- Mainstream UC/Video conferencing services
- Device: Compatible with Windows/Mac PCs, laptops, tablets and smartphones with full-featured USB-C

Compliance



Computer USB Type-C Specification

USB Type-C Connector		Data Transfer	Display	Power
USB 2.0 480 Mbps	 Normal	✓	✗	✗
	 PD enabled	✓	✗	✓
USB 3.1 Gen1 5 Gbps	 Normal	✓	✗	✗
	 PD enabled	✓	✗	✓
USB 3.1 Gen2 10 Gbps	 Normal	✓	✗	✗
	 PD enabled	✓	✗	✓
Display Port 5-10 Gbps	 Normal	✓	✓	✗
	 PD enabled	✓	✓	✓
Thunderbolt 20-40 Gbps PD enabled Display Port		✓	✓	✓

About LINKVIL

As a sub-brand of Fanvil, LINKVIL focuses on the research and development of A&V-IoT wireless communication products. Based on Audio & Video -IoT, LINKVIL helps customers to achieve full connection of wireless communication systems and will build a wireless communication Eco-system for multi-scenarios to help different industries accelerate their digital transformation.

Copyright

Copyright © 2025 Fanvil Link Technology Co., Ltd.

All rights reserved. No parts of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, photocopying, recording, or otherwise, for any purpose, without the express written permission of Fanvil Link Technology Co., Ltd.

More Information

The above specifications may be updated in the future without prior notice. All hardware/software/physical features should be based on the final shipped products.

For more information, please visit: www.fanvil.com



Fanvil Link Technology Co., Ltd.

Web: www.fanvil.com

Add: 13th Floor, Building 2, Runzhi R&D Center, Xin'an Street, Bao'an District,
Shenzhen, China

Copyright © 2025 Fanvil Link Technology Co., Ltd.